



## Anvil-RX takes rugged AI and high compute performance to new heights.

Connect Tech's Anvil-RX is a rugged embedded system powered by the NVIDIA® Jetson AGX Orin™. Fully IP67 rated, with M12 and sealed PC connectors, this powerful edge system can be deployed for mission critical applications in harsh environments. The Anvil-RX is ideal for AMR, robotics, agriculture, and industrial applications.



## FEATURES

- ✓ IP67 Rated
- ✓ 8x GMSL2 Camera Inputs
- ✓ 2x 10GBASE-T Ethernet (10Gbe)
- ✓ 2x 1000BASE-T Ethernet (1GbE)
- ✓ Rugged M12 Connectors
- ✓ Up to 2x NVMe (2/4/8TB)
- ✓ 2x USB 3.2, 2x CAN, HDMI, UART, GNSS

## SPECIFICATIONS

<b>AI Compute</b>	NVIDIA® Jetson AGX Orin™ 32GB NVIDIA® Jetson AGX Orin™ 64GB NVIDIA® Jetson AGX Orin™ Industrial	<b>AI Performance</b>	Jetson AGX Orin™ 32GB: 200 TOPS Jetson AGX Orin™ 64GB: 275 TOPS Jetson AGX Orin™ Industrial: 248 TOPS
<b>GPU</b>	Jetson AGX Orin™ Industrial, Jetson AGX Orin™ 64GB: 2048-core NVIDIA® Ampere architecture GPU with 64 Tensor Cores Jetson AGX Orin™ 32GB: 1792-core NVIDIA® Ampere architecture GPU with 56 Tensor Cores	<b>CPU</b>	Jetson AGX Orin™ Industrial, Jetson AGX Orin™ 64GB: • 12-core Arm® Cortex®-A78AE v8.2 64-bit CPU • 3MB L2 + 6MB L3 Jetson AGX Orin™ 32GB: • 8-core Arm® Cortex®-A78AE v8.2 64-bit CPU • 2MB L2 + 4MB L3
<b>Memory</b>	Jetson AGX Orin™ 32GB: 32GB 256-bit LPDDR5 - 204.8GB/s Jetson AGX Orin™ 64GB: 64GB 256-bit LPDDR5 - 204.8GB/s Jetson AGX Orin™ Industrial: 64GB 256-bit LPDDR5 (+ ECC) - 204.8GB/s	<b>Serial Interfaces</b>	• 2x UART (RS232/422/485 configurable) • 1x I2C Channel @ 3.3V IO • 1x SPI Channel @ 3.3V IO • 2x @3.3V levels UART1 and UART2 • 2x CAN Bus ports
<b>Storage</b>	• 64GB eMMC (on Jetson Module) • Up to 2x NVMe (2/4/8TB)	<b>USB</b>	2x USB 3.2 Ports (10Gbps Capable) • Sealed Connector
<b>Camera Inputs</b>	8x GMSL2 Camera Inputs (NOVA Orin Compliant)	<b>Video Output</b>	1x HDMI (Sealed Connector)
<b>Networking</b>	• 2x 10GBASE-T (10GbE) with optional PoE module • 2x 1000BASE-T (1GbE) • Connector: 4x M12 X-Code	<b>GPIO</b>	• 8x GPIO 3.3V Input/Output Capable pins • 2 x PWM Outputs 3.3V logic level • 1x 3.3V Power Pin at 1A
<b>Wireless</b>	• Dual Band WiFi 6E + BT 5.2 Module • 1x 5G/LTE (optional) • 1x RTK GNSS (optional)	<b>Input Power/Misc Power Details</b>	+18V to +60V (+9V to +60V and +9V to +36V options available)
<b>Dimensions</b>	279mm x 214mm x 145mm (10.98" x 8.43" x 5.71")	<b>Trusted Platform Module (TPM)</b>	SLB9670 TPM2.0 Chipset
<b>Weight</b>	TBD	<b>Operating Temperature</b>	-40°C to +65°C (-40°F to +149°F)
<b>Warranty and Support</b>	1 Year Warranty and Free Support		



Specifications subject to change without notice. ©2024 Connect Tech Inc. All trademarks are property of their respective holder. CTIX-00228(0.00) - 2024-06-11