


Boson for FRAMOS is an AI vision powerhouse, integrating up to four MIPI cameras within an extremely small footprint.

Specifically designed for use within the FRAMOS Sensor Ecosystem, Boson for FRAMOS maximizes sensor inputs and storage solutions for high-end vision applications. Compatible with multiple sensor modules and equipped with PC style connectors, Boson for FRAMOS will accelerate development of applications wishing to utilize multiple cameras on the Jetson platform.



Equipped with 4x FRAMOS PixelMate connectors for instant access to the entire FRAMOS Sensor Module Ecosystem.

Since Boson for FRAMOS is compatible with the Jetson Nano, TX2 NX, and Xavier NX modules, users can seamlessly transition between modules depending on their AI processing requirements.

FEATURES

- ✓ Dual Gigabit Ethernet and USB ports
- ✓ Dimensions: 90mm x 75mm
- ✓ Additional storage available through NVMe or a microSD card
- ✓ Supports multiple configurations for deployment flexibility. Options for 2 and 4 lane MIPI camera modules
- ✓ WiFi and Bluetooth expansion

SPECIFICATIONS WHEN USED WITH JETSON XAVIER NX MODULE

Ethernet	2x 1000BASE-T Ethernet Port <ul style="list-style-type: none"> • 1x Port sourced directly from NX • 1x Port sourced from i210 	MIPI Camera Inputs	Up to: <ul style="list-style-type: none"> • 4x 2-lane MIPI FRAMOS Sensor Modules, or • 3x 4-lane FRAMOS Sensor Modules
Storage	<ul style="list-style-type: none"> • 1x M.2 M-Key (2280) NVMe PCIe x4 (Gen 3) • 1x Micro SD Card 	M.2 E-Key	<ul style="list-style-type: none"> • 1x 2230 E-Key Expansion for WiFi/Bluetooth • 1x PCIe x1 + USB 2.0
USB	1x USB 3.2 Gen 2 w/ OTG capability (Type C) 1x USB 2.0 (Type A)	Input Power / Misc Power Details	+9V to +36V Input Voltage Range <ul style="list-style-type: none"> • Auto-ON operation by default
RTC Battery	1x RTC Battery External Connector	FAN	1x FAN w/ PWM Control
Operating Temperature	-40°C to +85°C (-40°F to +185°F)	Weight	80g (2.82oz)
Mechanical Details	90mm x 75mm (3.54" x 2.95")	Display Output	1x HDMI 2.0
Misc Interfaces	<ul style="list-style-type: none"> • 3x 3.3V TTL UARTs (1x CONSOLE) • 8 GPIOs 3.3V TTL (2x PWM Capable) • 2x I2C 3.3V • 1x CAN 2.0b • 2x SPI • 2x 3.3V • 2x 5V • 8x GND 	Warranty and Support	1 Year Warranty and Free Support