


**Boson for FRAMOS is an AI vision powerhouse, integrating up to four MIPI cameras within an extremely small footprint.**

Specifically designed for use within the FRAMOS Sensor Ecosystem, Boson for FRAMOS maximizes sensor inputs and storage solutions for high-end vision applications. Compatible with multiple sensor modules and equipped with PC style connectors, Boson for FRAMOS will accelerate development of applications wishing to utilize multiple cameras on the Jetson platform.



**Equipped with 4x FRAMOS PixelMate connectors for instant access to the entire FRAMOS Sensor Module Ecosystem.**

Since Boson for FRAMOS is compatible with the Jetson Nano, TX2 NX, and Xavier NX modules, users can seamlessly transition between modules depending on their AI processing requirements.

## FEATURES

- ✓ Supports multiple configurations for deployment flexibility. Options for 2 and 4 lane MIPI camera modules
- ✓ Additional storage available through NVMe or a microSD card
- ✓ Dimensions: 90mm x 75mm

## SPECIFICATIONS WHEN USED WITH JETSON NANO MODULE

<b>Ethernet</b>	1x 1000BASE-T Ethernet Port <ul style="list-style-type: none"> <li>• 1x Port sourced directly from Nano</li> </ul>	<b>MIPI Camera Inputs</b>	Up to: <ul style="list-style-type: none"> <li>• 4x 2-lane MIPI FRAMOS Sensor Modules, or</li> <li>• 3x 4-lane FRAMOS Sensor Modules</li> </ul>
<b>Storage</b>	<ul style="list-style-type: none"> <li>• 1x M.2 M-Key (2280) NVMe PCIe x4 (Gen 2)</li> <li>• 1x Micro SD Card</li> </ul>	<b>M.2 E-Key</b>	Not Supported
<b>USB</b>	1x USB 3.1 Gen 1 w/ OTG capability (Type C) 1x USB 2.0 (Type A)	<b>Input Power / Misc Power Details</b>	+9V to +36V Input Voltage Range <ul style="list-style-type: none"> <li>• Auto-ON operation by default</li> </ul>
<b>RTC Battery</b>	1x RTC Battery External Connector	<b>FAN</b>	1x FAN w/ PWM Control
<b>Operating Temperature</b>	-40°C to +85°C ( -40°F to +185°F)	<b>Weight</b>	80g (2.82oz)
<b>Mechanical Details</b>	90mm x 75mm (3.54" x 2.95")	<b>Display Output</b>	1x HDMI 2.0
<b>Misc Interfaces</b>	<ul style="list-style-type: none"> <li>• 3x 3.3V TTL UARTs (1x CONSOLE)</li> <li>• 8 GPIOs 3.3V TTL (2x PWM Capable)</li> <li>• 2x I2C 3.3V</li> <li>• 2x SPI</li> <li>• 2x 3.3V</li> <li>• 2x 5V</li> <li>• 8x GND</li> </ul>	<b>Warranty and Support</b>	1 Year Warranty and Free Support